MIRAI
by chimei

DTL-522P201

22" / 56 cm LCD TV

HD ready

HDMI

1680 x1050 WXGA+

ChroMAX circuitry

700 : 1 Contrast

5 ms Ultra Fast

1000 Teletext pages

MIRAI
by chimei

DTL-522P201
22" / 56 cm LCD TV

Screen Size	473.76(H) x 296.1(V)
Aspect Ratio	16 : 10
Pixel Pitch	0.282(H) x 0.282(V)mm
Panel Resolution	1680 x 1050
Brightness	300 cd/m^2
Contrast Ratio (typ.)	700 : 1
Response Time (typ.)	5 ms
Viewing Angles (typ.)	170°(H) / 160°(V)
Display Color	16.7 M
Tuner System	PAL, SECAM, NTSC Video
Standard TV	B/G, D/K, I, L/L'
Control Panel	Power(On/Off), Source Select(SCART 1/SCART 2/YPbPr/VGA/HDMI/TV),
	Menu(OSD) Operation, Channel Up, Channel Down,
	Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: S-RGB/AV(IN), TV(OUT)
	SCART 2: S-RGB/AV(IN), AV(OUT)
	VGA Input(YPbPr via VGA connector), PC Audio In (for VGA),
	HDMI, Headphone Output
Support Timing	480i, 480p, 576i, 576p, (HDTV) 720p, 1080i; VGA max. 1440 x 900 Resolution
	Recommended, 1680 x 1050 – Resolution supported but not recommended
Speaker	3W x 2
User Controls	Contrast, Brightness, Back Light, Saturation, Colour Temp,
	Red, Green, Blue, White Balance, Picture Mode, DCI, LTI,
	Auto(picture setup), Clock, Phase, H-Position, V-Position
	CH Scan, Program, Manual Scan, Update Scan,
	Audio(Balance, Bass, Treble), Language
Pic-Mode	Vivid / Movie / Sport / Game / User
Sleep Timer Function	Off / 15 min. / 30 min. / 60 min. / 90 min. / 120 min.
Teletext	1000 pages
Power Supply	AC 100-240 V, 1.5A, 50/60Hz
Power Consumption	Operation < 60W, Standby < 2W
Safety / EMC	CB, Intertek-GS, CE, RoHS, WEEE
Accessories	Remote Control, Batteries, User Manual, Power Cord, Power Adapter
VESA mounting	100 x 100 mm
System Dimension	539.7(W) x 437.2(H) x 182(T) mm
Carton Size	580(W) x 500(H) x 122(T) mm
N.W./G.W.	6.8 kg/8.8 kg

Jupiterstraat 82, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23-567 10 56 FAX +31 (0)23-567 10 66
info@nl-mirai.com

www.mirai.eu

E&OE